



MATERIAL SAFETY DATA SHEET

File NO:20140101-01



Product Name	Lithium Ion Battery
1. Product Identification;	
Product Name	Lithium Ion Battery
Company of Producing	BYD
Cell Type:	LP103450ARU
Watt-hour Rating:	6.11WH
2.Composition	Wt%
Lithium Cobalt Oxide	25-45
PVDF	0.5-2.0
Carbon	5-25
PTFE	0.5-2.0
Electrolyte(EC/EMC/DEC/1molLiPF6)	5-25
PP	1-5
Copper	5-25
Aluminum	10-30
Nickel	0.1-1.5

3.Hazard Identification

Material	Emergency Overview (Appearance)	Toxicity (Potential Health Effects)
Lithium Cobalt Oxide	Blue-Black Powder (odorless)	Cobalt and Cobalt compounds are considered to be possible human carcinogen(s) .By IARC: May irritate eyes, skin, nose ,throat, and respiratory system May cause allergic skin sensitization (rash).
Carbon	Black Powder (odorless)	No cases of carbon being harmful to humans have been reported. WHO and ILO have never verified that carbon irritation of the skin and mucous membrane, etc. In some individuals.
Bond	Odorless White Powder	Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material .As a finished product ,it is a synthetic, high molecular weight



BYD LITHIUM BATTERY CO., LTD.

CAUTION!
 MELT
 PROCESSING
 RELEASES
 VAPORS
 WHICH
 MAY
 CAUSE
 EYE,
 SKIN
 AND
 RESPIRATORY
 TRACT
 IRRITATION.

polymer . due to its chemical and physical properties , this material dos not require special handing other than the good industrial hygiene and safety practical employed with any industrial material of this type . Under normal processing conditions , this material release fame or vapor components of these release may vary with processing time and temperatures . These process releases may produce eye , skin and/or respiratory tract irritation and , with repeated or prolonged exposures .,nausea , drowsiness , headache and weakness Although unlikely under normal handling conditions , if this material is heated in excess of 600F(315C) hazardous , decomposition products will be produced . hazardous decomposition products include hydrogen fluoride and oxides of carbon , the concentrations of which vary with temperature and heating regimens

Electrolyte

Colorless Liquid
 WARNING!
 FLAMMABLE.
 REACTS WITH WSTER
 TO FORM
 HYDROFLUORIC ACID.
 MAY CAUSE BURNS TO
 SKIN AND EYES
 EFFECTS MAY BE
 DELEYED. MAY CAUSE
 BLINDNESS.
 PROBABLE
 REPRODUCTIVE
 HAZARD.

May cause moderate to severe irritation, burring , and dryness of the skin. May cause eye irritation or burning .Breathing of the mists, vapors or fumes may irritate the nose, throat and lungs or fumes may irritate the nose throat and lungs Exposure of material with areas which contain water may generate hydrofluoric acid which can cause immediate burns on skin, severe eye bums burns to the mouth and gastrointestinal tract if ingested, and laryngeal edema if inhaled. Direct exposure to areas of the body need to be treated immediately to prevent injury.

4. First Aid Measures



BYD LITHIUM BATTERY CO., LTD.

Eyes: Flush with water for at least 15 minutes. If irritation occurs and persists, contact a medical doctor.

Skin: Remove contaminated clothing and thoroughly wash with soap and plenty of water. If irritation persists, contact a medical doctor.

Inhalation: Remove to fresh air. If breathing difficulty or discomfort occurs and persists, see a medical doctor. If breathing has stopped, give artificial respiration and see a medical doctor IMMEDIATELY.

5. Fire Fighting Measures

Hazardous Combustion Products: When burned, hazardous products of combustion including fumes of carbon monoxide, carbon dioxide, and fluorine can occur

Extinguishing Media: Water, carbon dioxide, dry chemical, or foam.

Basic Fire Fighting Procedures: Wear NIOSH/MSHA approved positive pressure self-

contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual Fire & Explosion Hazards: This material does not represent an unusual fire or explosion hazard.

Autolgnition Temperature: No Data.

Flammability Limits in Air, Lower, % by Volume: 1.4

Flammability Limits in Air, Upper, % by Volume: 11

6. Accidental Release Measures

Procedure for Release and Spill:

Sweep up and place in a suitable container, Dispose or waste according to all local, state and Federal Laws and Regulations.

Before cleanup measures begin, review the entire MSDS with particular attention Potential Health Effects; and on Recommended Personal Protective Equipment.

7. Handling and storage

Material things Handling: Avoid contact with eyes, skin or clothing, use with adequate ventilation. Wear safety glasses and rubber gloves. Wash thoroughly after handling.

Material	Storage
Lithium Cobalt Oxide	Keep away from strong acids. Keep container closed.
Carbon	Store this material in a sealed enclosure to avoid dispersion of carbon fiber dust. Keep container closed.
Bond	Store in a cool, dry place. This material is not hazardous under normal storage condition; however, material should be stored in closed container, in a secure area to prevent



BYD LITHIUM BATTERY CO., LTD.

container damage and subsequent spillage.

Electrolyte

Store in tightly closed containers in a cool, dry, isolated, well-ventilated area away from heat, sources of ignition and in compatibles. Store in original container. Keep from freezing. Avoid exposure to high temperatures

Cell Handling

Technical measures

Prevention of user exposure : Not necessary under normal use.

Prevention of fire and explosion : Not necessary under normal use.

Precaution for safe handling : Do not damage or remove the external tube. Specific safe handling advice : Never throw out cells in a fire or expose to high

temperatures. Do not soak cells in water and seawater. Do not expose to strong

oxidizers. Do not give a strong mechanical shock or throw down. Never

disassemble, modify or deform. Do not connect the positive terminal to the

negative terminal with electrically conductive material. In the case of charging,

use only dedicated charger or charge according to the conditions specified by BYD.

Cell Storage

Technical measures

Storage conditions (suitable, to be avoid) : Avoid direct sunlight, high temperature, high humidity. Store in cool place (temperature : -20 ~ 35 degree C, humidity : 45~85%).

8. Exposure Controls/Person Protection.

Engineering controls: Investigate engineering techniques to reduce exposures use with adequate ventilation a Recommended personal protective Equipment

Eye/Face protection: Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely wear chemical goggles and have eye flushing equipment available

Skin protection: Minimize skin contamination by following good industrial hygiene practices Wearing protective gloves is recommended Wash hands and contaminated skin thoroughly after handling.

Respiratory protection: Avoid breathing dust and processing vapors When adequate ventilation is not available wear a NIOSH/MSHA respirator approved for protection against inorganic dusts.

Special clothing: Robber gloves.

Other: Quick-drench eye wash and safety shower.

9. Physical and Chemical Properties

Material	Appearance	Odor	Molecular Weight	Vapor Pressure
----------	------------	------	------------------	----------------



BYD LITHIUM BATTERY CO., LTD.

LiCoO ₂	Solid, Blue-Black Powder	Odorless	97.88	—
Carbon	Black Powder	Odorless	12.01	—
PTFE	Latex	Odorless	—	—
PVDF	Powder	Odorless	—	—
Copper	Metal	Odorless	63.55	—
Nickel	Metal	Odorless	58.69	—
Aluminum	Metal	Odorless	26.98	—
Electrolyte Colorless Liquid, with a mild (EC/DEC/EMC/1molLiPF ₆)		Volatile	organic odor	—
Material	Sublimating Point Gravity)	Freezing Point/ Melting Point	Solubility in water	Density (Specific
LiCoO ₂	—	>1000 deg.C (1280 deg.F)	Insoluble	—
Carbon	3000°C or more	—	Insoluble	2.2 g/ml
PTFE	—	—	Soluble	—
PVDF	— g/ml	165-172°C	Negligible	1.76-1.80
Copper	—	1083°C	Insoluble	8.96 g/ml
Nickel	—	1555°C	Insoluble	8.91g/ml
Aluminum Electrolyte	— 126°C (20/20°C)	660°C —	Insoluble Partial	2.7 g/ml 1.22
(EC/EMC/DEC/1molLiPF ₆)				WATER=1

10. Stability and Reactivity

Material	Stability	Incompatibility	Hazardous Polymerization	Hazardous Decomposition Products
LiCoO ₂	Stable	Acids	Dose not polymerize	None



BYD LITHIUM BATTERY CO., LTD.

Carbon	Stable	Strong oxidants	–	–
Bond carbon	Stable	Strong base, ester, Ketones, Silica, Titanium .	Dose not occur	HF, possible oxides of
Electrolyte compounds, monoxide	Volatile	Strong reducers, bases, strong acids, oxidizing agents, moist air or water.	Will not occur	Volatile pentafluoride Hydrogen fluoride, carbon Carbon dioxide and other decomposition product, etc.

- Cell Stability : Stable under normal use
- Hazardous reactions occurring under specific conditions
- Conditions to avoid : When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Direct sunlight and high humidity.
- Materials to avoid : Conductive materials, water, seawater, strong oxidizers and strong acids.
- Hazardous decomposition products : Acrid or harmful gas is emitted during fire.

11. Ecological Information

Eco Toxicological Information: No information available.

Chemical Fate Information: No data are available.

Environmental Effects: No data are available.

Toxicological Information

There is no data available on the product itself. The information of the internal cell materials is as follows.

Lithium cobaltic – LiCoO₂

- Acute toxicity : Unknown.
- Local effects : Unknown.
- Sensitization : The nervous system of respiratory organs may be stimulated sensitively.
- Chronic toxicity/Long term toxicity : By the inhalation of coarse particulate and steamy gas of cobalt, it is possible to cause the serious respiratory-organs disease. The person of allergy-natured or sensitive-natured may cause a skin reactionary lung disease.
 - Local effects(skin) : Although it is very rare, the rash of the skin and allergic erythema may result. Graphite
- Acute toxicity : Unknown.
- Local effects : Unknown.
- Chronic toxicity/Long term toxicity : Since the prolonged inhalation under the high concentration of a graphite coarse particulate may become a cause of a lung disease or a tracheal disease, it is regulated by the coarse particulate obstacle prevention rule and the dust-lung method enforcement regulations.
- Carcinogen city : Graphite is not recognized as a cause of cancer by research



BYD LITHIUM BATTERY CO., LTD.

5	External Short	Pass	
6	Impact	Pass	
7	Overcharge	Pass	
8	Forced Discharge	N/A	

16. Other Information

The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.

This safety data sheet provides guidance on health. Safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

17. Reference

Chemical substances information: Japan Advanced Information center of Safety and Health International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Centre (CIS)

1999 TLVs and BEIs: American Conference of Governmental Industrial Hygienists (ACGIH)

Dangerous Goods Regulations: 55th Edition of IATA DGR Effective 1 January 2014: International Air Transport Association (IATA)

IMDG CODE 2012 Effective 1 January 2014: International Maritime Organization (IMO)

GB12268 Effective 1 December 2012: Standardization Administration of the People's Republic of China

MSDS of raw materials by prepared by the manufactures

;last data revised 2014-1-1

The material safety data sheet is furnished to every manufacturer as a reference to secure the safe handling of chemical. Every manufacturer is requested to carry out appropriate actions for chemical handling as their own responsibility. The supplier makes no warrantee, either express or implied. concerning of this products. User assumes all risks resulting from its use.

For more information contact:

Technology Manager

BaoPing road, Baolong

Longgang Shenzhen ,518116 ,

P.R .China

Tel:+86-755-8988 8888

Fax: +86-755-8964 3262

<http://www.byd.com>